



Data sheet

Dygestorium Compact Line DCL 18.00 SS WALK-IN



Standard equipment:

- illumination of working chamber
- air-flow sensor (Schneider FM 550-A-0-E)
- Declaration of conformity CE: PN-EN 14175; PN-EN 14727; PN-EN 14056; PN-EN 13150

Additional options:


- electrical sockets
- cold water tap





A. POLOK – KOWALSKA, S. KOWALSKI 44-300 WODZISŁAW ŚLĄSKI, UL. KOKOSZYCKA 172 C

TECHNICAL DATA - DIMENSIONS overall dims [mm]		
height B	2385-2870	
depth C	1200	
working space dims (mm)		
width D	1470	
window width D1	1410	
height E	2145	
depth F	845	



TECHNICAL DATA	
recommended airflow [m3/h]	900 - 1500
nominal power [W]	82
voltage**	230 VAC 50Hz
diameter of the air outlet stub [mm]	200
airflow sensor (Schneider FM 550-A-0-E)	compliance with PN-EN 14175-2
electrical insulation	class I
required capacity of the ventilation system	0,3 - 0,5 [m/s]
standard ventilation system	double rear wall
frame and housing material	The frame is made entirely of galvanized steel. External housing made of galvanized and painted with epoxy paint steel
working chamber wall finishing	galvanized steel painted with epoxy paint

