

## **GW2145**



LABORATORY GLASSWARE WASHER BASIC LINE - GLASSWARE WASHER 45 CM Download PDF

- ✓ washing up to 95°C antibacterical thermal disinfection
- programs: 9 default + 6 custom
- microprocessor programmable electronic control
- ✓ serial port RS232 for connection to external printer or PC
- ✓ active thermodynamic drying
- alkaline powder detergent dispenser
- peristaltic pump for acid liquid neutralizer
- possibility of installing 1 additional peristaltic pump
- ✓ washing chamber and internal door in AISI 316L stainless steel
- external panels made of AISI 304 stainless steel
- n. 2 independent washing levels through telescopic guides
- external dimensions LxDxH: 450 x 620 x 850 mm
- ✓ internal working dimensions LxDxH: 370 x 480 x 570 mm
- incorporated water softener with salt sensor
- cold water and demineralized water connections
- electronic door lock system for user safety
- electrical connection: 1/N/PE 230 V 50 Hz 3,3 kW max
- ✓ 60 Hz version available
- Schuko plug 16 A 250 V included
- ✓ upper and lower trolleys D-CS1 and D-CS2 included

Smeg S.p.A. Via Leonardo Da Vinci, 4 - 42016 Guastalla (RE) Italy - P. IVA 01555030350 Phone +39 0522 8211 - fax +39 0522 821453 - service.instruments@smeg.it

