

Data sheet

Ultra-Low Freezer ZLN-UT 200 VIP Smart



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART controller:

- 4,3", clear, full colour touch screen
- LAN, USB ports for data transfer
- multi-segment time and temperature programs
- visual and sound alarm
- internal memory for programs and data storage
- event registry
- user manual for direct download
- Quick change of program parameters - Alarm Bar
- operating with gloves on



Smart - preview screen




tel. (+48) 32 453 91 70



A. POLOK – KOWALSKA, S. KOWALSKI 44-300 WODZISŁAW ŚLĄSKI, UL. KOKOSZYCKA 172 C

TECHNICAL DATA	
air convection	natural
chamber capacity [I]	259
number of boxes 133x133x50mm [pcs]	192
controller	microprocessor PID
display	4,3" full colour touch screen
insulation type	vacuum - VIP panels
TEMPERATURE	
temperature range [°C]	-8650
temperature resolution every [°C]	0,1
cooling time from +20°C to -80°C [min]	160
heating time in case of power failure -80°C to -60°C [min]	50
temperature fluctuation at -80°C [+/-°C]*	1,5
temperature variation at -80°C [+/-°C]*	4,0
CHAMBER	
door type	solid
interior	
C Smart	stainless steel to DIN 1.4016
P Smart	DIN 1.4301
housing	
C Smart	powder coated sheet
P Smart	powder coated sheet

overall dims [mm] /1/	
width A	880
height B	1390
depth C	960
internal dims [mm]	
width D	620
height E	770
depth F	580
height I	360



shelves (standard max)	2/2
max shelf workload [kg] /2/	10
number of internal chambers	2
max unit workload [kg]	65
weight [kg]	200



A. POLOK – KOWALSKA, S. KOWALSKI 44-300 WODZISŁAW ŚLĄSKI, UL. KOKOSZYCKA 172 C

ELECTRICAL PARAMETERS		
voltage**	230V 50-60Hz	
nominal power [W]	2100	
refrigerant	R290 / GWP=3 R170 / GWP=6	
warranty	24 months	
manufacturer	POL-EKO-APARATURA	

all the above technical data refer to standard units (without optional accessories)

K = +/- (T average max. - T average min.) / 2

OPTIONS AND ACCESSORIES

LAB DESK	Order numberLabDesk	LabDesk software
ALARM	Order number: PORT ALARM	Dry alarm contact
USB	Order number: USBK	USB cable
LAN	Order number: LANK	LAN cable
(((●)))	Order number: KD	Access control



st - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:

^{** -} other power supplies on request

^{1 -} depth doesn't include 50 mm of power cable